

## Safety valve SVH/E 1/2" 3 bar

- For heating systems with output up to 50 kW
- Maximum pressure: 3 bar
- Inlet connection: internal thread G 1/2"
- Outlet connection: internal thread G 3/4"



Code

SVH/E 1/2-3B

## Safety valve SVH/E 3/4" 3 bar

- For heating systems with output up to 100 kW
- Maximum pressure: 3 bar
- Inlet connection: internal thread G 3/4"
- Outlet connection: internal thread G 1"



SVH/E 3/4-3B

## Safety valve SVH/E 1" 3 bar

- For heating systems with output up to 200 kW
- Maximum pressure: 3 bar
- Inlet connection: internal thread G 1"
- Outlet connection: internal thread G 1 1/4"



SVH/E 1-3B

## Safety valve SVH/E 1 1/4" 3 bar

- For heating systems with output up to 350 kW
- Maximum pressure: 3 bar
- Inlet connection: internal thread G 1 1/4"
- Outlet connection: internal thread G 1 1/2"



SVH/E 5/4-3B

## Safety valve SVE/SOL 1/2" 6 bar

- For solar heating systems with up to 50 kW output and solar panel surface up to 50 m<sup>2</sup>
- Maximum pressure: 6 bar
- Inlet connection: internal thread G 1/2"
- Outlet connection: internal thread G 3/4"



SVE/SOL 1/2-6B

## Safety valve SVW 1/2" 10 bar

- For sanitary system with rated power up to 75 kW and flow rate up to 200 liters
- Maximum pressure: 10 bar
- Inlet connection: internal thread G 1/2"
- Outlet connection: internal thread G 3/4"



SVW 1/2-10B